

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
26 February 2004 (26.02.2004)

PCT

(10) International Publication Number  
WO 2004/016839 A1

(51) International Patent Classification<sup>7</sup>: D01D 5/26

108-1303 Hansin Apt., Cheongnyangni 1-dong Dongdaemun-gu, Seoul 130-775 (KR).

(21) International Application Number:  
PCT/KR2003/001403

(74) Agents: LEE, Sang-Yong et al.; 4F., Byukcheon Bldg., 1597-5, Seocho-dong, Seocho-gu, Seoul 137-876 (KR).

(22) International Filing Date: 16 July 2003 (16.07.2003)

(25) Filing Language: Korean

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:  
10-2002-0048594 16 August 2002 (16.08.2002) KR

(71) Applicant (*for all designated States except US*):  
SAMSHIN CREATION CO., LTD. [KR/KR]; 31-28 Cheongdam2-dong, Gangnam-gu, Seoul 135-950 (KR).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): CHUN, Suk-Won [KR/KR]; 9-507 Byeoksan Apt., Suyu 2-dong Gangbuk-gu, Seoul 142-771 (KR). PARK, Jong-Su [KR/KR];

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: APPARATUS FOR PRODUCING NANOFIBER UTILIZING ELECTROSPINNING AND NOZZLE PACK FOR THE APPARATUS



(57) Abstract: The apparatus for producing a nanofiber includes a supply unit (110) for supplying melted polymer for fiber material, a spinning unit (122) having several radiation nozzles (122) to which first voltage having a polar is applied to discharge the polymer solution supplied from the supply unit in a filament form, a collector (130) spaced apart from the spinning nozzles in order to pile the filament from the spinning unit and applied to second voltage having opposite polar to the first voltage, and a control unit (140) applied to the first voltage having the same polar as the charged filament and extended from an end of the spinning nozzle toward the collector at least at both sides of the spinning unit in order to prevent repulsion and dispersion of the filament stream radiated from each spinning nozzle.